



Phoenix Automation

Horeca & Retail



Fec 80T bonprinter



De Fec 80T van Firich geeft de gebruiker de beste kwaliteit voor de beste prijs. Deze thermische printers hebben een printsnelheid van 150 mm per seconde. De Fec 80T garandeert u efficiency en gemak voor uw bedrijfsvoering.

Specs

Printer	
Printer Method	Direct Thermal
Printing Speed	150 mm/sec (About 35.5 IPS)
Dot Density	180 DPI
Dot Pitch	0.141 mm
Effective Printing Width	72 mm, 512 dots/line
Character Per Line	Front A 42 columns Front B 56 columns Big5, GB, Kanji 21 columns
Paper Specification	
Paper Type	Thermal Paper / Roll type
Paper Width	79.5 mm ± 0.5 mm
Paper Thickness	0.06 ~ 0.08 mm
Paper Roll Diameter	Max. 81.0 mm
Roll Core Inner Diameter	12.5 mm ± 0.5 mm
Paper Supply Method	D&P (Drop and Print) Mechanism
Character Set	
Alphanumeric Character	95
Extended Graphic	128 x 7 pages (a space page)
International Character	32
Barcode	EAN-8, EAN-13, CODE 39, CODE 128, ITF, UPC-A, CODABAR
Emulation	TM-T88III (ESC/POS Command Compatible)
Driver	Win 2K/XP/VISTA OPOS driver
Draw Port	2 ports
Interface	RS-232C (standard), Centronics (IEEE 1284) USB, Ethernet, WiFi, Combo